


Economy Solution For Powered Door Operators




Swinging Doors



Bi-Parting Sliding Doors



Single Sliding Doors



Standard or High Lift Doors



Full Lift Doors

R-Plus Doors combines the high-quality of an R-Plus door with a LiftMaster Model T power door operator to create a low cost solution. This NEMA 1-rated solution is for indoor applications not needing a pedestrian door capability or mounting inside a freezer. Covering door sizes up to 10x10 feet, this operator works well in areas that do not encounter the harsh environments requiring a NEMA 4 rating.

The LiftMaster Model T is an industrial-duty trolley operator featuring a low profile and industrial ball bearings on the output shaft for a smooth, long-lasting movement. Standard features on this low-cost unit include a safety-edge stop and a single-button security-protected remote that handles complete OPEN/CLOSE/STOP operations. Programming is easy, with diagnostic LEDs to guide installation and troubleshooting.

Standard Features

Motor: Continuous-duty high-starting torque motor with instant reverse and overload protection. 3/4 HP single- or three-phase.

Drive Reduction: First-stage heavy-duty 5L V-belt; second-stage #41 chain.

Manual Disconnect: Spring-loaded for manual operation.

External Radio Control Terminal: Quick, convenient connections for retrofitting or adding radio controls on logic or mechanical operators.

Bearings: Ball bearings on output shaft; heavy-duty, oil-filled bushings on reduction shafts.

Brake: Solenoid-actuated brake is standard.

Safety Edge: Stops and reverses door on contact with obstruction in door opening.


Construction: NEMA 1 type electrical box, heavy-duty 11-gauge steel frame with durable powdercoat finish, all reduction sprockets drilled and pinned to shafts.

Warranty: 2-year warranty, Serviceable by commercial door companies nationwide who are familiar with LiftMaster controllers

Voltages Available:

115V single-phase	208/230V 3-phase
230V single-phase	460V 3-phase

A real added advantage is the existing nationwide group of experienced commercial door companies ready to service LiftMaster controllers. Combined with an R-Plus door, this operator is a complete low-cost package that maintains traditional R-Plus high-quality standards in low-use and small-door settings.



Logic Features

Logic 3.0 Technology (L3):

Built-in 3-channel, 315MHz radio receiver accepts up to 23 Security+® or unlimited DIP switch remotes. Single-button remote handles OPEN/CLOSE/STOP operations.

Maintenance Alert System™ establishes a routine maintenance schedule based on the number of cycles or calendar date. Includes self-diagnostic system that allows you to troubleshoot up to eight different error codes.

Reliability & Programming Simplicity:

Diagnostic LEDs speed installation and troubleshooting.

Industrial linear contactor provides significantly longer control runs than conventional contactors.

Options

Motor covering: matches door finish

Dual pull-cord activation: low temperature-rated

R-PLUS
COLD STORAGE DOORS
A Division of Imperial Manufacturing, Inc.